

VPN Connections

Glossary

Product Documentation



Copyright Notice

©2013-2019 Tencent Cloud. All rights reserved.

Copyright in this document is exclusively owned by Tencent Cloud. You must not reproduce, modify, copy or distribute in any way, in whole or in part, the contents of this document without Tencent Cloud's the prior written consent.

Trademark Notice



All trademarks associated with Tencent Cloud and its services are owned by Tencent Cloud Computing (Beijing) Company Limited and its affiliated companies. Trademarks of third parties referred to in this document are owned by their respective proprietors.

Service Statement

This document is intended to provide users with general information about Tencent Cloud's products and services only and does not form part of Tencent Cloud's terms and conditions. Tencent Cloud's products or services are subject to change. Specific products and services and the standards applicable to them are exclusively provided for in Tencent Cloud's applicable terms and conditions.

Glossary

Last updated : 2019-12-13 20:07:34

Customer Gateway

A customer gateway is a VPC gateway that is mapped to the IPsec VPN gateway in your IDC. It must be used with a VPN gateway. Encrypted VPN tunnels can be established between a VPN gateway and multiple customer gateways.

IPsec VPN

An IPsec VPN is an encrypted tunnel over a public network that is used to connect your IDC and a VPC.

Route Table

A [route table](#) consists of a series of routing policies that are used to define the traffic direction of each subnet within the VPC. A subnet can be associated with only one route table, but a route table can be associated with multiple subnets in the same VPC.

Routing Policy

A [routing policy](#) defines a path that network traffic goes through. Each routing policy comprises three parameters:

1. Destination: Describes the destination IP range. The destination cannot be an IP range in the VPC where the route table resides.
2. Next hop type: Specifies the next hop type for a VPC, for example, **Public Gateway**, **VPN Gateway**, or **Direct Connect Gateway**. You must create such a gateway before you select the next hop type.
3. Next hop: Specifies the next hop gateway to which the traffic of a subnet associated with the route table will be directed.

VPC

A Virtual Private Cloud (VPC) is a separate network space in Tencent Cloud, which is similar to a traditional network running in your IDC. However, the services hosted in a VPC are your Tencent Cloud services, including: [Cloud Virtual Machine \(CVM\)](#), [Cloud Load Balancer](#), and [TencentDB](#). You do not need to worry about the procurement and OPS of network devices, but can customize IP ranges, IP addresses, and routing policies by using software. You can use [EIPs](#), [NAT gateways](#), and [public gateways](#) to flexibly access the Internet or connect a VPC to your IDC through [VPN](#) or [Direct Connect](#). In addition, by using the [peering connections](#) of a Tencent Cloud VPC, you can easily provide a unified server for global access and three IDCs in two regions for disaster recovery. You can also use the [security groups](#) and [network ACLs](#) of the VPC to ensure comprehensive network security.

VPN Gateway

A [VPN gateway](#) is an IPsec VPN gateway in a VPC. It is used with a customer gateway (the IPsec VPN gateway in your IDC) to enable secure and reliable encrypted network communication between the VPC and your IDC.

VPN Tunnel

A [VPN tunnel](#) is an encrypted IPsec VPN tunnel over a public network. After the VPN gateway and customer gateway are created, a VPN tunnel can be established for encrypted communication between the VPC and your IDC.

Subnet

A [subnet](#) is an IP range that is flexibly planned in a VPC. Applications and services can be deployed in different subnets to securely and flexibly host multi-layer web applications in the VPC.