

StreamLive

Introduction

Product Documentation



Copyright Notice

©2013-2019 Tencent Cloud. All rights reserved.

Copyright in this document is exclusively owned by Tencent Cloud. You must not reproduce, modify, copy or distribute in any way, in whole or in part, the contents of this document without Tencent Cloud's the prior written consent.

Trademark Notice

 Tencent Cloud

All trademarks associated with Tencent Cloud and its services are owned by Tencent Cloud Computing (Beijing) Company Limited and its affiliated companies. Trademarks of third parties referred to in this document are owned by their respective proprietors.

Service Statement

This document is intended to provide users with general information about Tencent Cloud's products and services only and does not form part of Tencent Cloud's terms and conditions. Tencent Cloud's products or services are subject to change. Specific products and services and the standards applicable to them are exclusively provided for in Tencent Cloud's applicable terms and conditions.


Introduction

Last updated : 2021-08-17 15:01:21

Overview

StreamLive is a premium stream processing platform newly launched by Tencent Cloud, which provides broadcast-grade live stream processing services. It enables you to create high-quality video streams and distribute them to various types of devices.

StreamLive uses Tencent Cloud's proprietary high-performance video encoding and compression algorithms to reduce transfer traffic consumption while delivering a better watch experience. In addition, it guarantees a 24/7 availability.



Features

Multi-Protocol and Multi-Format Stream Input

StreamLive supports multiple streaming protocols such as RTP, RTMP, UDP, HLS, HTTP-MP4, and RTP-FEC. It provides both pull and push input methods. When RTP MPEG-TS is used, StreamLive allows the video stream input

with multiple audio tracks (language type) and can transcode each track separately.

High-Quality and Multi-Format Transcoding

StreamLive supports transcoding at different resolutions (SD, HD, UHD, 2K, 4K, etc.), bitrates, and frame rates. It also provides high-performing Top Speed Codec Transcoding. After this feature is enabled, AI algorithms can calculate the optimal dynamic encoding parameters in real time based on business scenarios, and implement low-bitrate as well as high-quality transcoding services.

Digital Rights Management (DRM)

StreamLive offers a specialized digital rights management (DRM) solution to fully protect your video assets. It supports FairPlay and Widevine encryption technologies, meeting the needs for digital copyright protection.

Multi-Protocol and Multi-Method Output

StreamLive supports various output muxing types, such as adaptive bitrate HLS, DASH, COS ARCHIVE, and StreamPackage.

Flexible Configuration for Independent Channels and Diverse Output Combinations

StreamLive provides services based on channel management, where the same channel can be configured with different inputs and outputs. You can associate an output with existing audio and video transcoding templates, configuring flexible output combinations to implement adaptive bitrate video delivery.

Stream Quality Monitoring

StreamLive offers detailed health reports about the running status of each channel and displays alerts, allowing you to check video stream quality in real time.

High Performance

Under the dual standards of SSIM and VMAF, Tencent Cloud Top Speed Codec Transcoding greatly outperforms AWS Elemental MediaLive Quality-Defined Variable Bitrate.

Low Costs

The characteristics of Top Speed Codec Transcoding meet the needs of customers for reducing the CDN bandwidth costs, which can still deliver a leading performance when the bitrate is reduced by about 10%.

Architecture Design

Each StreamLive channel supports dual-pipeline input configuration at the beginning of the input configuration, where pipeline A is required and pipeline B is optional.

Pipeline A and pipeline B operate independently, that is, the streams from input A will be output to the destination A of each output group, while the streams from input B will be output to the destination B of each output group.

StreamLive Channel

